TC2MHR036-F



High resolution bi-telecentric lens for 1" detectors, magnification 0.353x, F-mount

SPECIFICATIONS

Magnification

	(X)	
Image circle Ø	(mm)	16.7
Object field of view 8		
with KAI-2020 14.8 mm diagonal w x h 11.84 x 8.88	(mm x mm)	33.5 x 25.2
with KAI-04050 16 mm diagonal w x h 12.8 x 9.6	(mm x mm)	36.3 x 27.2
with KAI-4022/4021 21.5 mm diagonal w x h 15.2 x 15.2	(mm x mm)	Ø=43.1
with KAI-08050 22.6 mm diagonal w x h 18.1 x 13.6(7)	(mm x mm)	Ø=38.5
Optical specifications		
	(mm)	102.56
Optical specifications Working distance (1) f/# (2)	(mm)	102.56 16
Working distance (1) f/# (2)	(mm) (deg)	
Working distance (1)		16
Working distance (1) f/# (2) Telecentricity typical (max) (3)	(deg)	16 < 0.08 (0.10)

0.353

(x)

(mm)

(mm)

(g)

168.7

64 701







NOTES

Mass

Length (6)

Diameter

Mechanical specifications

- 1. Working distance: distance between the front end of the mechanics and the object. Set this distance within +/- 3% of the nominal value for maximum resolution and minimum distortion.
- 2. Working F-number: the real F-number of a lens when used as a macro. Lenses with smaller apertures
- 3. Maximum slope of chief rays inside the lens: when converted to milliradians, it gives the maximum measurement error for any millimeter of object displacement. Typical (average production) values and maximum (guaranteed) values are listed.
- 4. Percent deviation of the real image compared to an ideal, undistorted image: typical (average production) values and maximum (guaranteed) values are listed.
- 5. At the borders of the field depth the image can be still used for measurement but, to get a perfectly sharp image, only half of the nominal field depth should be considered. Pixel size used for calculation is 5 um.
- $\,$ 6. Measured from the front end of the mechanics to the camera flange.
- 7. With KAI-08050 (22.6 mm diagonal) detectors, the FOV of TC4MHR yyy lenses may show some vignetting at the image corners, as these lenses are optimized for 1.2" detectors (21.5 mm diagonal).
- 8. For the fields with the indication "Ø =", the image of a circular object of such diameter is fully inscribed into the detector.

COMPATIBLE PRODUCTS



LTCLHP036-G Telecentric HP illuminator, beam diameter 45 mm, green



CMHO036 Clamping mechanics for TCxx036 lenses and LTCLHP036-X illuminators



LTRN036NW Ring LED illuminator, white