


Telecentric lenses | TC series | TC 23 240

TC 23 240

Bi-telecentric lens for 2/3" detectors, magnification 0.037 x, C-mount

Magnification	(x)	0.037
Image circle	(mm)	11.0
Object field of view		
with 1/3" detector (4.8 x 3.6 mm)	(mm x mm)	130.8 x 98.1
with 1/2.5" detector (5.70 x 4.28 mm)	(mm x mm)	155.4 x 116.6
with 1/2" detector (6.4 x 4.8 mm)	(mm x mm)	174.4 x 130.8
with 1/1.8" detector (7.13 x 5.37 mm) (7)	(mm x mm)	194.3 x 146.3
with 2/3" - 5 Mpx detector (8.45 x 7.07 mm)	(mm x mm)	230.2 x 192.6
Optical specifications		
Working distance (1)	(mm)	500.0
f/# (2)		8
Telecentricity typical (max) (3)	(deg)	< 0.03 (0.08)
Distortion typical (max) (4)	(%)	< 0.04 (0.08)
Field depth (5)	(mm)	498
CTF @ 70 lp/mm	(%)	> 45
Dimensions		
Mount		C
Length (6)	(mm)	775.1
Diameter	(mm)	322
Weight	(g)	20800



NOTES

- 1. Working Distance: distance between the front lens and the object. Set this distance within +/- 3% of the nominal value for maximum resolution and minimum distortion.
- 2. Working F-number: the real F-number of a lens when used as a macro. Lenses with smaller apertures can be supplied on request.
- 3. Maximum slope of chief rays inside the lens: when converted to millirad, it gives the maximum measurement error for any millimeter of object displacement. Typical (average production) values and maximum (guaranteed) values are listed.
- 4. Percent deviation of the real image compared to an ideal, undistorted image: typical (average production) values and maximum (guaranteed) values are listed.
- 5. At the borders of the field depth the image can be still used for measurement but, to get a very sharp image, only half of the nominal field depth should be considered.
- 6. Measured from the front end of the mechanics to the camera flange.
- 7. With 1/1.8" (9 mm diagonal) detectors, the FOV of TC12 yyy lenses may show some vignetting at the image corners, as these lenses are optimized for 1/2" detectors (8 mm diagonal).
- 8. For the fields with the indication "Ø =", the image of a circular object of such diameter is fully inscribed into the detector.

COMPATIBLE PRODUCTS



LTCLHP240-G
Telecentric HP illuminator, beam diameter 300 mm, green