

## P/N: T911307ACC

### Copyright

© 2020, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

### Document identity

Publ. No.: T911307ACC  
 Commit: 60099  
 Language: en-US  
 Modified: 2019-10-03  
 Formatted: 2020-10-27

### Website

<http://www.flir.com>

### Customer support

<http://support.flir.com>

### Disclaimer

Specifications subject to change without further notice. Camera models and accessories subject to regional market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations. Please refer to [exportquestions@flir.com](mailto:exportquestions@flir.com) with any questions.



General description	
This cable is used to connect the infrared camera to Ethernet networks. One connector is a screw connector.	
Physical data	
Weight	0.068 kg (0.15 lb.)
Cable length	2.0 m (6.6 ft.)
Connector	RJ-45 to RJ-45 screw connector
Cable type	CAT-6
Shipping information	
Packaging, type	Cardboard box
Packaging, weight	0.267 kg (0.59 lb.)
Packaging, size	243 × 165 × 85 mm (9.6 × 6.5 × 3.3 in.)
EAN-13	7332558010914
UPC-12	845188011710
Country of origin	China

### Compatible with the following products:

- 48201-1001; FLIR A300
- 42701-1001; FLIR A300 (9 Hz)
- 48201-1101; FLIR A310
- 42701-1101; FLIR A310 (9 Hz)
- 48001-1101; FLIR A315
- 48201-1201; FLIR A320 Tempscreen
- 42701-1201; FLIR A320 Tempscreen (9 Hz)
- 48001-1001; FLIR A325sc